

# Xerox<sup>®</sup> Phaser<sup>®</sup> 6510 Color Printer



System Specifications	Phaser 6510N	Phaser 6510DN	Phaser 6510DNI
One-sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 30 ppm color and black and white Up to 24 ppm color and black and white Up to 28 ppm color and black and white		
Two-sided Speed 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	NA  Up to 18 ppm color and black and white  Up to 17 ppm color and black and white  Up to 19 ppm color and black and white		
Monthly Duty Cycle <sup>1</sup>	Up to 50,000 pages / month		
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 3,000 pages		
Processor	733 MHz		
Memory	1 GB		
Connectivity	10/100/1000Base-T Ethernet High-Speed USB 3.0		10/100/1000Base-T Ethernet High-Speed USB 3.0 Wi-Fi 802.11n Wi-Fi Direct®
Paper Handling			
Bypass Tray			
Capacity <sup>3</sup>	50 sheets	50 sheets	
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14	in. / 76 x 127 mm to 216 x 356 mm	
Weights	16 lb. bond to 58 lb. cover / 60 to	220 gsm	
Mediα Types	Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled		
Tray 1			
Capacity <sup>3</sup>	250 sheets		
Sizes	Custom Sizes 3 x 5.8 in. to 8.5 x 14 in. / 76 x 147 mm to 216 x 356 mm		
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm		

Mediα Types	Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled
Optional Tray 2	
Capacity <sup>3</sup>	550 sheets
Sizes	Custom Sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 191 mm to 216 x 356 mm
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm
Media Types	Bond Plain Card Stock Custom Glossy Card Stock Hole punched Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled
Total Capacity	
Device Standard Capacity <sup>3</sup>	300 sheets
Device Total Capacity <sup>3</sup>	850 sheets
Paper Output	
Output Capacity <sup>3</sup>	150 sheets
Automatic 2-Sided	NA Standard
Device Specifications	
Electrical Requirements	
North America	Voltage: 120 VAC +/- 10 % Frequency: 60 Hz +/- 3 Hz, 12A
Europe	Voltage: 220-240 VAC +/- 10 % Frequency: 50 Hz +/- 3 Hz, 6A
Power Consumption	
Operation <sup>4</sup>	120V: Maximum 380 watts 220V: Maximum 350 watts
Standby Mode <sup>4</sup>	120V: Maximum 41 watts 220V: Maximum 44 watts
Power Off Mode <sup>4</sup>	120V: Maximum 0.2 watts 220V: Maximum 0.3 watts
Sleep Mode <sup>4</sup>	120V: Maximum 0.9 watts 220V: Maximum 1.0 watts
Warm-up (from Sleep Mode)	As fast as 26 seconds
Operating Environment	
<b>Required Temperature Range</b> Storage	-4°F to 104°F / -20°C to 40°C

Operating	41°F to 90°F / 5°C to 32°C	
Required Relative Humidity	15 % to 85 %	
Sound Power Levels Operating Standby	6.76 B or less 4.00 B or less	
Sound Pressure Levels Operating Standby	51.9 dB(A) or less 24.9 dB(A) or less	
Dimensions and Weights (unpac	kaged)	
Phaser 6510N, and DN	Width: 16.5 in. / 420 mm Depth: 19 in. / 483 mm Height: 13.7 in. / 347 mm Weight: 52.5 lb. / 23.8 kg	
Phaser 6510DNI	Width: 16.5 in. / 420 mm Depth: 19.6 in. / 499 mm Height: 13.7 in. / 347 mm Weight: 52.5 lb. / 23.8 kg	
550-sheet Paper Tray	Width: 16.5 in. / 420 mm Depth: 18.3 in. / 465 mm Height: 5.9 in. / 150 mm Weight: 14.8 lb. / 6.7 kg	
Dimensions and Weights (packag	ged)	
Phaser 6510N, DN and DNI	Width: 14.3 in. / 634 mm Depth: 22.8 in. / 580 mm Height: 19.9 in. / 505 mm Weight: 64.4 lb. / 29.2 kg	
550-sheet Paper Tray	Width: 21.1 in. / 535 mm Depth: 23 in. / 584 mm Height: 9.8 in. / 248 mm Weight: 18.7 lb. / 8.5 kg	
System Certification/Regulatory	Compliance	
	c TUV us FCC 47CFR15-B ICES/NMB-3 "A" CE NOM EAC UkrSepro BIS GS Citrix™ Certified Cerner Apple® AirPrint® certification Google Cloud Print™ Certification Mopria® certified Wi-Fi Alliance Certified Blue Angel MEDITECH ENERGY STAR® ECOLOGO® EPEAT (United States) To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.	
Print		
First-print-out Time	As fast as 12 seconds color and black and white	
Print Resolution	Up to 1200 x 2400 dpi	
Page Description Languages	Adobe® PostScript® 3™ PCL® 5e, 6	

	PDF TIFF	
Maximum Print Area	4 mm edge of paper	
Print Features	Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Color Calibrated Solid-color Simulations Personal Print Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks	
Print from USB	Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS	
Operating Systems	Windows®, 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.10 and higher Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10 Fedora Core 12-15 SUSE®	
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD SMB SMTP, Secure SMTP LDAP, Secure LDAP Bonjour® / AirPrint® FTP Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP v2/3, WINS, DHCP Autonet, TLS, SNTP, MDNS	
Font Capability	136 PostScript fonts 88 PCL fonts	
Mobile Solutions and Mobile Dev	ice Apps	
Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Apple <sup>®</sup> AirPrint <sup>®</sup>	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other webconnected device.	

Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers.  You can easily print photos, Web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.	
Xerox® Wireless Print Solutions Adapter (Optional)	The Xerox® Wireless Print Solutions Adapter seamlessly connects your Xerox® printer or MFP to modern mobile and desktop workflows, regardless of your office environment. For more information, visit www.xerox.com/WPSA	
Xerox® Print Management and Mobility Suite, Xerox® Print Management and Mobility Service	Xerox® Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.	
Security		
Security Features	Simultaneous HTTP and HTTPS support IPsec 802.1x Authentication S/MIME IP Filtering Secure Print SNMP v3 LDAP (SASL)	
Device Management		
Xerox® CentreWare® Web		
	<ul> <li>A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>	
Xerox® Embedded Web Server - Ir	ntegrated Device Web Page	
Device Status	<ul> <li>Tray status/contents</li> <li>Consumables status</li> <li>Billing/Usage</li> <li>Quick Links</li> </ul>	
Job Submission	Print-ready files (PS, PCL®, PDF, XPS, JPEG)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device.	
Browsers	Microsoft® Internet Explorer 11 Microsoft Edge™ 38 Mozilla™ Firefox® 48 Apple® Safari® 9.1 Google Chrome™ 52	
Remote Print Services		
Xerox® MeterAssistant® Service	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Xerox® SuppliesAssistant® Service	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
Maintenance Assistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.	

What's In The Box	
	<ul> <li>Phaser 6510 Color Printer</li> <li>Standard Capacity Print cartridge: One of each (Cyan, Magenta, Yellow: 1,000 print capacity<sup>5</sup>; Black: 1,500 print capacity<sup>5</sup></li> <li>Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers and Warranty Statement)</li> <li>Installation Guide</li> <li>Quick Use Guides</li> <li>Power cord</li> </ul>

Supplies and Accessories	Quantity	Part Number		
Supplies				
Extra-High Capacity Print Cartridges	Cyan: 4,300 standard pages <sup>5</sup> Magenta: 4,300 standard pages <sup>5</sup> Yellow: 4,300 standard pages <sup>5</sup>	106R03690 106R03691 106R03692		
High Capacity Print Cartridges	Black 5,500 standard pages <sup>5</sup> Cyan: 2,400 standard pages <sup>5</sup> Magenta: 2,400 standard pages <sup>5</sup> Yellow: 2,400 standard pages <sup>5</sup>	106R03480 106R03477 106R03478 106R03479		
Standard Capacity Print Cartridges	Black: 2,500 standard pages <sup>5</sup> Cyan: 1,000 standard pages <sup>5</sup> Magenta: 1,000 standard pages <sup>5</sup> Yellow: 1,000 standard pages <sup>5</sup>	106R03476 106R03473 106R03474 106R03475		
Drum Cartridges	Black: 48,000 pages <sup>6</sup> Cyan: 48,000 pages <sup>6</sup> Magenta: 48,000 pages <sup>6</sup> Yellow: 48,000 pages <sup>6</sup>	108R01420 108R01417 108R01418 108R01419		
Waste Cartridge	30,000 pages <sup>6</sup>	108R01416		
Accessories				
550-sheet Paper Tray		097S04765		
Wireless Network Adapter		497K16750		

<sup>&</sup>lt;sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office

Configurations vary by geography.



<sup>&</sup>lt;sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>4</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

<sup>5</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

<sup>6</sup> Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.