

Xerox[®] WorkCentre[®] 6515 Color Multifunction Printer



System Specifications	WorkCentre 6515N	WorkCentre 6515DN	WorkCentre 6515DNI	
One-sided Speed 8.5 x 11 in. 8.5 x 14 in. / 216 x 356 mm A4 / 210 x 297 mm	Up to 30 ppm Color and Black and White Up to 24 ppm Color and Black and White Up to 28 ppm Color and Black and White			
Two-sided Speed 8.5 x 11 in. 8.5 x 14 in. / 216 x 356 mm A4 / 210 x 297 mm	NA	Up to 18 ppm Color and Black and White Up to 17 ppm Color and Black and White Up to 19 ppm Color and Black and White		
Monthly Duty Cycle ¹	Up to 50,000 pages / month			
Recommended Average Monthly Print Volume ²	Up to 3,000 pages			
Processor	1.05 GHz	1.05 GHz		
Memory	2 GB			
Connectivity	10/100/1000Base-T Ethernet High-Speed USB 3.0		10/100/1000Base-T Ethernet High-Speed USB 3.0 Wi-Fi 802.11n Wi-Fi Direct®	
Paper Handling				
Document Feeder				
Capacity ³	Single-pass Duplex Automat	Single-pass Duplex Automatic Document Feeder (DADF): 50 sheets		
Sizes	Custom Sizes: 5.5 x 5.5 in. to	Custom Sizes: 5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 216 x 356 mm		
Weights	16 lb. bond to 45 lb. cover / 60 to 125 gsm			
Bypass Tray				
Capacity ³	50 sheets			
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm			
Weights	16 lb. bond to 58 lb. cover / 60 to 220 gsm			

Media Types	Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled		
Tray 1			
Capacity ³	250 sheets		
Sizes	Custom Sizes 3 x 5.8 in. to 8.5 x 14	4 in. / 76 x 147 mm to 216 x 356 mm	
Weights	16 lb. bond to 65 lb. cover / 60 to	176 gsm	
Media Types	Bond Plain Card Stock Custom Envelopes Glossy Card Stock Hole punched Labels Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled		
Optional Tray 2			
Capacity ³	550 sheets		
Sizes	Custom Sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 191 mm to 216 x 356 mm		
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm		
Media Types	Bond Plain Card Stock Custom Glossy Card Stock Hole punched Letterhead Lightweight Cardstock Lightweight Glossy Card Stock Preprinted Recycled		
Total Capacity			
Device Standard Capacity ³	300 sheets		
Device Total Capacity ³	850 sheets		
Paper Output			
Output Capacity ³	150 sheets	150 sheets	
Automatic 2-Sided	NA	Standard	

Device Specifications		
Electrical Requirements		
North America	Voltage: 120 VAC +/- 10% Frequency: 60 Hz +/- 3 Hz, 12A	
Europe	Voltage: 220-240 VAC +/- 10 % Frequency: 50 Hz +/- 3 Hz, 6A	
Power Consumption		
Operation ⁴	120V: Maximum 350 watts 220V: Maximum 370 watts	
Standby Mode ⁴	120V: Maximum 51 watts 220V: Maximum 52 watts	
Power Off Mode ⁴	120V: Maximum 0.2 watts 220V: Maximum 0.3 watts	
Sleep Mode ⁴	120V: Maximum 1.1 watts 220V: Maximum 1.2 watts	
Warm-up (from Sleep Mode)	As fast as 27 seconds	
Operating Environment		
Required Temperature Range Storage Operating	-4°F to 104°F / -20°C to 40°C 41°F to 90°F / 5°C to 32°C	
Required Relative Humidity	15% to 85%	
Sound Power Levels Operating Standby	6.84 B or less 4.25 B or less	
Sound Pressure Levels Operating Standby	52.5 dB(A) or less 26.3 dB(A) or less	
Dimensions and Weights (unpackaged)		
Workcentre 6515N, DN, and DNI	Width: 16.5 in. / 420 mm Depth: 19.9 in. / 506 mm Height: 19.7 in. / 500 mm Weight: 67.7 lb. / 30.7 kg	
550-sheet Paper Tray	Width: 16.5 in. / 420 mm Depth: 18.3 in. / 465 mm Height: 5.9 in. / 150 mm Weight: 14.8 lb. / 6.7 kg	
Dimensions and Weights (packaged)		
Phaser 6510N, DN and DNI	Width: 25 in. / 634 mm Depth: 22.8 in. / 580 mm Height: 26 in. / 659 mm Weight: 79.8 lb. / 36.2 kg	
550-sheet Paper Tray	Width: 21.1 in. / 535 mm Depth: 23 in. / 584 mm Height: 9.8 in. / 248 mm Weight: 18.7 lb. / 8.5 kg	

System Certification/Regulatory (Compliance	
Certifications	C TUV us FCC 47CFR15-B ICES/NMB-3 "A" CE NOM EAC UkrSepro BIS GS FCC 47CFR68 ISED DC-01 Citrix™ Certified Cerner Apple® AirPrint® certification Google Cloud Print™ Certification Mopria® certified Wi-Fi Alliance Certified Blue Angel MEDITECH ECOLOGO® EPEAT (United States) ENERGY STAR® To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.	
Сору		
Document Scanner	Single-pass Duplex Automatic Document Feeder (DADF) with 50-sheet capacity	
Document Scanner Size	Platen: Up to 8.5 x 11.7 in / A4 DADF: 8.5 x 14 in. / 216 x 356 mm	
Simplex Speed	Black and White: Up to 21 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm Color: Up to 13 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	
Duplex Speed	Black and White: Up to 9 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm Color: Up to 8 cpm (copies per minute) 8.5 x 11 in. / A4 / 210 x 297 mm	
First-Copy-Out Time	As fast as 12 seconds from the Platen	
Sides (input:output)	1:1, 1:2, 2:2, and 2:1	
Quantity	1 to 999	
Resolution	Up to 600 x 600 dpi	
Reduction/Enlargement	Variable zoom from 25 % to 400 % in 1 % increments	
Concurrency	Concurrent scanning and printing	
Copy Features	Automatic Background Suppression Book Copying Book Copying with Center Erase Collation Darkness Control Edge Erase ID Card Copy N-up Reduce/Enlarge (25 % -400 %) Image Shift Original Type Sample Copy Sharpness	
Print		
First-print-out Time	As fast as 12 seconds Color and Black and White	
Print Resolution	Up to 1200 x 2400 dpi	

Page Description Languages	Adobe® PostScript® 3™ PCL® 5e, 6 PDF TIFF
Maximum Print Area	4 mm edge of paper
Print Features	Banner Sheets Booklet Print Cover / Separators Draft Mode Fit to Page N-up Overlays PANTONE® Color Calibrated Solid-color Simulations Personal Print Proof Print RAM Collation Run Black Saved Print Secure Print Watermarks
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS
Operating Systems	Windows®, 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2008 R2, Server 2012 Mac OS® version 10.10 and higher Citrix® Redhat® Enterprise Linux® IBM® AIX® 5 HP-UX® 11iv2 Oracle® Solaris 9, 10 Fedora Core 12-15 SUSE®
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD SMB SMTP, Secure SMTP LDAP, Secure LDAP Bonjour® / AirPrint® FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP v2/3, WINS, DHCP Autonet, TLS, SNTP, MDNS
Font Capability	136 PostScript fonts 88 PCL fonts
Mobile Solutions and Mobile Dev	ice Apps
Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Apple [®] AirPrint [®]	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other webconnected device.

Xerox [®] Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.	
Xerox [®] Mobile Link App (Free at Google Play™ Store and Apple [®] App Store)	The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer.	
Xerox® Wireless Print Solutions Adapter (Optional)	The Xerox® Wireless Print Solutions Adapter seamlessly connects your Xerox® printer or MFP to modern mobile and desktop workflows, regardless of your office environment. For more information, visit www.xerox.com/WPSA	
Xerox® Print Management and Mobility Suite, Xerox® Print Management and Mobility Service	Xerox® Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.	
Scan		
Capability	Color and Black-and-white	
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs	
Input Speed - Black and White	Scan up to 37 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm	
Input Speed - Color	Scan up to 21 ipm – 8.5 x 11 in. / A4 / 210 x 297 mm	
Resolution	Optical – 600 x 600 dpi	
Bit Depth	24-bit Color / 8-bit Grayscale	
Maximum Scan Area	Platen: Up to 8.5 x 11.7 in. / A4 Document Feeder: Up to 8.5 x 14 in. / 216 x 356 mm	
Network Filing Protocol	FTP SMTP SMB/SMB2	
File Formats	JPG Single-page and Multi-page TIFF PDF Searchable PDF with integrated OCR	
Scan Driver Compatibility	WIA TWAIN	
Supported Scan Destinations	Scan to Email (local address book or LDAP integration) Scan to Network (via FTP/SMB) Scan to USB Memory Device Scan to Email (SMTP) Scan to WSD Scan to Application (TWAIN Network) Scan to WIA (WSD Scan) Scan to Mac 10.9 or later (Network/Mac ICA) Scan to Network Computer (SMB/FTP) Scan to Multiple Destinations in a Single Scan Job	

Security		
Security Features	Simultaneous HTTP and HTTPS support IPsec 802.1x Authentication S/MIME IP Filtering Secure Print Secure Fax Receive SNMP v3 LDAP (SASL) Network Authentication Kerberos Authentication (Unix / Linux / Windows ADS)	
Fax ⁵		
Fax Speed	33.6 Kbps	
Memory	4 MB	
Resolution	Up to 400 x 400 dpi	
Compression	MH/MR/MMR/JBIG	
Fax Features	Broadcast Sending (up to 200 destinations) Delayed Start (up to 24 hours) Fax Address Book (up to 200 speed dials) Fax Forward to Email Fax Forwarding and Local Print Polling Receive Reject Junk Fax Secure Fax Receive	
Device Management		
Xerox® CentreWare® Web		
	 A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 	
Xerox® Embedded Web Server - Ir	ntegrated Device Web Page	
Device Status	 Tray status/contents Consumables status Billing/Usage Quick Links 	
Job Submission	Print-ready files (PS, PCL®, PDF, XPS, JPEG)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device.	
Browsers	Microsoft® Internet Explorer 11 Microsoft Edge™ 38 Mozilla™ Firefox® 48 Apple® Safari® 9.1 Google Chrome™ 52	
Remote Print Services		
Xerox [®] MeterAssistant [®] Service	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Xerox® SuppliesAssistant® Service	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
Maintenance Assistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.	

What's In The Box	
	 WorkCentre 6515 Color Multifunction Printer Standard Capacity Print cartridge: One of each (Cyan, Magenta, Yellow: 1,000 print capacity⁶; Black: 1,500 print capacity⁶ Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord Fax cord

Supplies and Accessories	Quantity	Part Number
Supplies		
Extra-High Capacity Print Cartridges	Cyan: 4,300 standard pages ⁶ Magenta: 4,300 standard pages ⁶ Yellow: 4,300 standard pages ⁶	106R03690 106R03691 106R03692
High Capacity Print Cartridges	Black 5,500 standard pages ⁶ Cyan: 2,400 standard pages ⁶ Magenta: 2,400 standard pages ⁶ Yellow: 2,400 standard pages ⁶	106R03480 106R03477 106R03478 106R03479
Standard Capacity Print Cartridges	Black: 2,500 standard pages ⁶ Cyan: 1,000 standard pages ⁶ Magenta: 1,000 standard pages ⁶ Yellow: 1,000 standard pages ⁶	106R03476 106R03473 106R03474 106R03475
Drum Cartridges	Black: 48,000 pages ⁷ Cyan: 48,000 pages ⁷ Magenta: 48,000 pages ⁷ Yellow: 48,000 pages ⁷	108R01420 108R01417 108R01418 108R01419
Waste Cartridge	30,000 pages ⁷	108R01416
Accessories		
550-sheet Paper Tray		097S04765
Wireless Network Adapter		497K16750

 $^{^{\}rm 1}$ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis. $^{\rm 2}$ Expected regular monthly throughput.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com



³ Paper capacities are based on 20 lb. /75 gsm stock; capacities will vary with different weight stocks.
⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Requires analog phone line.

Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.